

ITW Permatex
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924 (ChemTel)
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 133K ANTI-SEIZE LUBRICANT 8OZ
Item No: 80078
Product Type: Lubricant

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | Weight% | ACGIH; TLV-TWA | OSHA PEL |
|--|---------|---------------------|----------------------|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5 | 40-60 | Not listed | Not listed |
| CALCIUM OXIDE 1305-78-8 | 15-25 | 2 mg/m ³ | 5 mg/m ³ |
| GRAPHITE 7782-42-5 | <10 | 2 mg/m ³ | 15 mg/m ³ |
| ALUMINIUM POWDER 7429-90-5 | <10 | 1 mg/m ³ | 15 mg/m ³ |
| MINERAL OIL 8012-95-1 | <5 | Not listed | Not listed |

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. May cause nose, throat and respiratory irritation. May cause gastrointestinal irritation. High concentrations may cause central nervous system (CNS) depression.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Overexposure may cause eye and skin redness, difficulty breathing and vomiting. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation.

| Component | Weight% | NTP | ACGIH Carcinogens | IARC Carcinogen |
|--------------------------|---------|-----|--|--|
| MINERAL OIL 8012-95-1 | <5 | | A2 Suspected human carcinogen (poorly and mildly refined); A4 not classifiable as a human carcinogen (highly and severely refined) | Group 3 Supplement 7, 1987, Monograph 33, 1984 |

Aggravated Medical Condition: Persons with respiratory problems such as emphysema and asthma should avoid inhalation. Since this product contain copper compounds, individuals with Wilson's Disease should avoid exposure to this product.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. If symptoms persist, call a physician.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >200° F TCC
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

5. FIRE FIGHTING MEASURES

Hazardous Products of Combustion: Oxides of carbon, Metal oxide fumes
 Unusual Fire/Explosion Hazards: May ignite when sufficient heat is applied.

Lower Explosive Limit: Not determined
 Upper Explosive Limit: Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).
 Handling: Avoid prolonged skin contact. Keep away from eyes. Do not inhale vapors. Do not use near heat, sparks or open flame. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses
 Skin: Neoprene or nitrile gloves recommended.
 Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
 Respiratory Protection: Not required under normal use. An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Silver paste
 Odor: Petroleum distillates
 Boiling Point: Not determined
 pH: Does not apply
 Solubility in Water: Nil
 Specific Gravity: 1.17
 VOC(Wt.%): 0
 Vapor Pressure: <5 mm Hg
 Vapor Density (Air=1): <1
 Evaporation Rate: <1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
 Hazardous Polymerization: Will not occur
 Incompatibilities: Strong oxidizers, alkalis, mineral acids, selected amines.
 Conditions to Avoid: Heat
 Hazardous Products of Combustion: Oxides of carbon, Metal oxide fumes

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
 US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)
 U.S. Department of Transportation - DOT - 49 CFR (Ground)

DOT Shipping Name: Not regulated
 Hazard Class: None
 UN/ID Number: None

IATA (Air)

Proper Shipping Name: Not regulated

14. TRANSPORTATION INFORMATION

Class or Division: None
UN/ID Number: None

IMDG (Vessel)

Proper Shipping Name: Not regulated
Hazard Class: None
UN Number: None

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

California Proposition 65: No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

HMIS is a registered trademark of the National Paint and Coatings Association

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106
Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: February 09, 2012
Revision Number: 1