

Perlator®

Faucet Aerator - 2.2 gpm

Flow Restricted Regular Size

NEOPERL®


flow, stop and go®

Features and Benefits

- Watercolours® design: Color coding to identify flow rate and stream pattern.
- Patented construction provides a splash-free stream, well-aerated and soft to the touch.
- Integrated anti-liming honeycomb replaces conventional wire mesh screens prone to lime build up.
- Anti-clogging dome screen filters sediment and particles.
- Compatible with regular and vandal proof M22 & M24 metric housings.
- Available housing finishes: chrome, polished brass, brushed nickel and oil rubbed bronze.
- Laser marked housings with statutory marks.

Certifications

ANSI/NSF®-61-372
ASME A112.18.1M and CSA B125



Thread & Part Number

Part #	Designation	Thread Size
10 935	Insert only	
10 900	Regular male	15/16"-27
10 910	Regular female	55/64"-27
10 920	Regular dual thread	15/16"-27 x 55/64"-27
10 904	Vandal proof regular male	15/16"-27
10 914	Vandal proof regular female	55/64"-27
10 926	Vandal proof regular dual thread	15/16"-27 x 55/64"-27

Other product combinations available.


Packaging:

Inserts 1 pc (bag), 6 pcs (bag), 50 pcs (bag)
Reg. male/female/dual thread 1 pc (bag), 6 pcs (tube), 50 pcs (tray)
Reg. vandal proof male/female/dual thread 1 pc (bag), 6 pcs (tube), 40 pcs (tray)

Color Code

Dome	Ring	Basket
Red	Red	Dark Gray

Flow Rate Curve



Dimensions

No	mm	In
A	20.88	.822
B	12.00	.472
C	19.97	.786
D	≈ 13	≈ 1/2


Housings



Technical Data

Materials: Body Acetal
Washer EPDM

Continuous



Short-term (5 minutes max.)
Per ASME A112.18.1 testing requirements.

