

PCA® Perlator®

Laminar Stream - 1.5 gpm max

Pressure Compensating Regular Size




flow, stop and go®

Features and Benefits

- ▶ Watercolours® design: Color coding to identify flow rate and stream pattern.
- ▶ Patented construction provides a splash-free, crystal clear (non-aerated) stream.
- ▶ Pressure compensating for constant flow from 20 to 80 psi.
- ▶ Recommended for use in healthcare facilities to prevent mixing air and water.
- ▶ Integrated anti-liming honeycomb replaces conventional wire mesh screens prone to lime build up.
- ▶ Anti-clogging dome screen filters sediment and particles.
- ▶ Compatible with regular and vandal proof M22 & M24 metric housings.
- ▶ Available housing finishes: chrome, polished brass, brushed nickel and oil rubbed bronze.
- ▶ Laser marked housings with statutory marks.

Certifications

ANSI/NSF®-61-372
 ASME A112.18.1M and CSA B125
 Meets **CALGreen** requirements
 WaterSense



Thread & Part Number

Part #	Designation	Thread Size
11 335	Insert only	
11 300	Regular male	15/16"-27
11 310	Regular female	55/64"-27
11 320	Regular dual thread	15/16"-27 x 55/64"-27
11 304	Vandal proof regular male	15/16"-27
11 314	Vandal proof regular female	55/64"-27
11 326	Vandal proof regular dual thread	15/16"-27 x 55/64"-27

Other product combinations available.


Packaging:

Inserts *1 pc (bag), 6 pcs (bag), 50 pcs (bag)*
 Reg. male/female/dual thread *1 pc (bag), 6 pcs (tube), 50 pcs (tray)*
 Reg. vandal proof male/female/dual thread *1 pc (bag), 6 pcs (tube), 40 pcs (tray)*

Color Code

Dome	Flow Regulator	Basket
Clear	Green	Light Gray

Flow Rate Curve



Dimensions

No	mm	In
A	20.88	.822
B	12.00	.472
C	19.97	.786
D	≈ 13	≈ 1/2

Housings



Technical Data

Materials: Body Acetal
 O-ring EPDM
 Washer EPDM

Continuous		Short-term (5 minutes max.) Per ASME A112.18.1 testing requirements.	
max. 60 °C	max. 140 °F	max. 70 °C	max. 160 °F
90 psi max.	6.2 bar max.	125 psi max.	8.5 bar max.

NEOPERL, Inc., Waterbury, CT • Tel: 203-756-8437 • Fax: 203-574-2107 • www.neoperl.com